



ENABLING BUSINESS
ANYTIME, ANYWHERE

BluPrints:Desktop Receipt Thermal Printer Series

BluPrints is an R&D driven company with the vision to provide innovative, agile and customized product solutions to our customers.

We specialize in Smart Printing Solutions. Reliable and easy to use, these state-of-the-art Mobile Thermal Printers deliver on-demand receipt/label printing anywhere, anytime.

BluPrints desktop thermal receipt printers are compact, durable, and easy to setup-use-maintain. This high speed, high resolution print & image printing device, with cash drawer interface are designed to keep up with your high business demand.

Ideally for application that require continuous printing at retail outlets, restaurants, shopping malls, supermarkets, hospitals, petrol pumps, toll, queue management etc.



Contact Us

Aadharshila Mobility Solutions Pvt Ltd
Aadharshila Mobility Solutions Pvt Ltd
Shed 63, Hartron Complex,
Sector-18 Electronic City.
Gurgaon 122015

www.bluprints.in

T: +91 9560188277/8447741431

E: info@bluprints.in, sales@bluprints.in

Technical Specifications

Item		Parameter
Printing parameter	Printing method	Thermal printing
	Resolution	203DPI, 8 dots/mm
	Printing width	25.4mm-110mm(832 dots)
	Printing speed	Max: 150 mm/s
	Interfaces	Standard: USB interface Optional: Serial/Ethernet ports Optional Wireless Communication: Wi-Fi,Bluetooth,or GPRS
Command set	/	ESC/POS compatible commands
Storage	RAM	8MB, receive buffer area 1M bytes
	FLASH	16MB, NV bitmap 64K bytes
Bar codes	1D	UPC-A、UPC-E、EAN-8、EAN13、CODE39、ITF、CODEBAR、CODE128、CODE93
	2D	QR Code、PDF417
Detection function	Sensor	Paper out, cover opened, label gap detection
LED indicator	Power indicator	Green
	Paper out indicator	Red
	Error indicator	Red
Paper Requirement	Type	Standard thermal label/receipt paper
	Width	25.4-110mm
	Thickness	0.056~0.1mm
	Diameter	100mm(Max)
Physical characteristics	Paper loading	Easy paper loading
	Paper cutting	Manual
	Operating condition	-10°C~ 50°C 25% ~ 80%RH
	Storage condition	-40°C~ 70°C ≤93%RH(40°Q
	Outline dimension	175mm×170mm×135mm(L×W×H)
	Weight	2.0Kg
Reliability	TPH life	100km
Software function	Driver procedure	Windows (WIN7/WIN8/WIN10/Vista/XP/2000)
Power Supply	Printer	Input: 24VDC/2A
	Power Adapter	Input: 100-240VAC, 50/60Hz, 2A